



# STANDARD FEATURES - 2008 MY

Effective 09/17/07

2600 North Highway  
Colville, WA 99114 • PH: 800-326-6594 • FAX: 509-684-5875

## ALASKAN

	240 AK SR	260 AK SR
"std" = standard; "n.a." = not available; "n.c." = no charge.		
Anodes: zinc, on port & stbd, mounted	std	std
Bilge Pumps: (2) - 2nd pump with auto-float switch	1250	1250
Bow Eyes: double, welded	std	std
Bow Floor Trim:	.125 aluminum	diamond plate
Bow Rails: welded, 12" tall	std	std
Cleats: qty on gunwale, qty on bow	8 / 1	8 / 1
Cup Holders: 2 on port dash	std	std
Decals & Striping: graphic w/ wide stripe	std	std
Fishbox: in transom with large lid and dividers (US/Imp gals)	47 / 38 gal	47 / 38 gal
Fishbox in floor: 54", aft of bulkhead (52 gals US)	std	std
Fuel Tank: (US/Imp gals)	127 / 106 gal	127 / 106 gal
Glove box: lockable	std	std
Handles: grab style - port and stbd (depends on cabin config)	std	std
Handles: grab style, welded - port & stbd	std	std
Hardtop: with sliding windows and locking bulkhead door	std	std
Horn: flush mount	std	std
Instrument Panel: 5 sealed Carling™ Contura rockers	std	std
- Fuel gauge and dash space for add'l gauges	std	std
- Power Point and 6 gang expansion fuse block	std	std
Lights: nav - port & starboard front windshield corners	std	std
Lights: anchor - rear of hard top, removable	std	std
Lights: 4, inside of hardtop (ceiling)	std	std
Paint: 2 pt Polyurethane, lite gray on deck, gunwales, and sides	std	std
Rails on hardtop: 4" high, welded w/2-stanchions	std	std
Rope Locker: in bow floor w/ alum hatch, notch for deck line	aluminum	diam. plate
Scupper Drains: in bow - 2" x 4" oblong hole	std	std
Steering: no-feedback	std	std
Steering Wheel: 15" w/ rubber coating, stainless steel	std	std
Stern Eyes: 1 pair	std	std
Storage Nets for under console	std	std
Transducer Bracket: port & stbd side (1 pair)	std	std
Transom - extended bracket* - 25", no kicker step	std	std
Trim Tabs: electric - 12" x 12" (1 pair)	std	std
Windshield Wipers: driver & passenger - 20" blade and arm	std	std
<b>Seats, Storage and Canvas:</b>		
Seats: Hi-Back, swivel (1 pair) locking on driver's side.	std	std
Seat Springs: horseshoe style (1 pair)	std	std
Storage: dry seat box with lid	std	std
Storage: 2 trays aft of bulkhead - port and stbd	std	std
Storage: lockable cabinets aft of bulkhead - port & stbd	std	std
Storage: hinged diamond plate step between consoles	std	std
Storage: in floor - inside of hardtop (depends on tank size)	36"	48"
Storage: shelves inside of hardtop	std	std

**NOTE: \*ET can only accommodate twin 25" motors**