



STANDARD FEATURES - 2008 MY

Effective 09/17/07

2600 North Highway
Colville, WA 99114 • PH: 800-326-6594 • FAX: 509-684-5875

OPEN FISHERMAN

"std" = standard; "n.a." = not available; "n.c." = no charge.	160 OF SM	180 OF SM	200 OF SM
Bilge Pump: (gph)	1250	1250	1250
Bilge Pump Pre-wiring: for auto float	std	std	std
Bow Eyes: double, welded	std	std	std
Bow Floor: welded aluminum, accepts ped-base	std	std	std
Cleats: 5 ea. Welded - 4 on gunwales, 1 on bow inwale	std	std	std
Decals & Striping; graphic w/ wide stripe	std	std	std
Fishbox: in floor, removable w/ handle (US/Imp gallons)	20 /17 gal	20 /17 gal	20 /17 gal
Fuel Tank: in bow, aluminum (US/Imp gallons)	24 / 20 gal	24 / 20 gal	24 / 20 gal
Fuel Tank Cover: diamond plate	std	std	std
Handle: grab style - starboard side, aft (1 ea)	std	std	std
Instrument Panel: 5 sealed Carling™ Contura rockers	std	std	std
- Fuel gauge on panel	std	std	std
- Power Point and 6 gang expansion fuse block	std	std	std
Lights: nav, in bow - plug in	std	std	std
Lights: anchor, at stern - removable	std	std	std
Paint: 2 pt Polyurethane, lite gray on deck, gunwales, and sides	std	std	std
Rod Grippers: 6 pair (3 port, 3 stbd)	std	std	std
Stern Eyes: (1 pair)	std	std	std
Storage: in bow floor	std	std	std
Storage Tray: port and starboard sides	std	std	std
Transom style: 20.5" with 8.0" step (for 20" motor shaft)	std	std	std
Transducer Bracket: 1 on stbd side	std	std	std

**** CANADIAN DEALERS:** Additional grab handles are required for 160 (2) and 180 (4) Open Fisherman models to meet Canadian Coast Guard 6 person capacity requirements.