


PRO V




MEASUREMENT	200 PV
Length	20' 4"
Total length	20' 4"
Beam (in)	94
Dead Rise: Forward X Amidship X Aft (degrees)	30 X 15 X 14
Bottom Dimensions: Thickness X Width (in)	0.19 X 72
Side Dimensions: Thickness X Height (in)	0.1 X 32
Transom Dimensions: Width X Height (in)	94 X 25.5
Person Capacity: Quantity X Weight (lbs)	7 X 1155
Maximum Fuel Capacity (gal)	48
Maximum Horsepower (HP)	175
Maximum Capacity (lbs)	1962
Boat Dry Weight (lbs)	1700
Fishing Cockpit: Width X Length (in)	80 X 152
Seat-to-Transom: Length (in)	112
Bow Length (in)	36

* Recommendations only for boats over 20'

NOTE: Measurements are approximations only. Variations will occur due to tolerances in manufacturing


PRO V HARD TOP



MEASUREMENT	200 PV HT
Hard Top Type	SLC
Length	20' 4"
Total length	20' 4"
Beam (in)	94
Dead Rise: Forward X Amidship X Aft (degrees)	30 X 15 X 14
Bottom Dimensions: Thickness X Width (in)	0.19 X 72
Side Dimensions: Thickness X Height (in)	0.1 X 32
Transom Dimensions: Width X Height (in)	94 X 25.5
Person Capacity: Quantity X Weight (lbs)	6 X 990
Maximum Fuel Capacity (gal)	48
Maximum Horsepower (HP)	175
Maximum Capacity (lbs)	1947
Boat Dry Weight (lbs)	1850
Fishing Cockpit: Width X Length (in)	80 X 78
Seat-to-Transom: Length (in)	112
Bow Length (in)	36
Cabin: Width X Length (in) X Height (in)	79.5 X 80 X 70

* Recommendations only for boats over 20'
 NOTE: Measurements are approximations only. Variations will occur due to tolerances in manufacturing

PRO V W/ EXTENDED TRANSOM




MEASUREMENT	180 PV ET	200 PV ET
Length	18' 5"	20' 5"
Total length	20' 8"	22' 8"
Beam (in)	94	94
Dead Rise: Forward X Amidship X Aft (degrees)	30 X 15 X 14	30 X 15 X 14
Bottom Dimensions: Thickness X Width (in)	0.19 X 72	0.19 X 72
Side Dimensions: Thickness X Height (in)	0.1 X 32	0.1 X 32
Transom Dimensions: Width X Height (in)	94 X 25.5	94 X 25.5
Person Capacity: Quantity X Weight (lbs)	7 X 1155	8 X 1320
Maximum Fuel Capacity (gal)	48	48
Maximum Horsepower (HP)	175	200
Maximum Capacity (lbs)	2070	2662
Boat Dry Weight (lbs)	1725	1925
Fishing Cockpit: Width X Length (in)	80 X 138	80 X 162
Seat-to-Transom: Length (in)	98.5	122.5
Bow Length (in)	36	36

* Recommendations only for boats over 20'

NOTE: Measurements are approximations only. Variations will occur due to tolerances in manufacturing

PRO V HARD TOP W/ EXTENDED TRANSOM



MEASUREMENT	180 PV ET HT	200 PV ET HT
Hard Top Type	SLC	SLC
Length	18' 5"	20' 5"
Total length	20' 8"	22' 8"
Beam (in)	94	94
Dead Rise: Forward X Amidship X Aft (degrees)	30 X 15 X 14	30 X 15 X 14
Bottom Dimensions: Thickness X Width (in)	0.19 X 72	0.19 X 72
Side Dimensions: Thickness X Height (in)	0.1 X 32	0.1 X 32
Transom Dimensions: Width X Height (in)	94 X 25.5	94 X 25.5
Person Capacity: Quantity X Weight (lbs)	6 X 990	7 X 1155
Maximum Fuel Capacity (gal)	48	48
Maximum Horsepower (HP)	175	200
Maximum Capacity (lbs)	2070	2662
Boat Dry Weight (lbs)	1725	1925
Fishing Cockpit: Width X Length (in)	80 X 138	80 X 162
Seat-to-Transom: Length (in)	98.5	122.5
Bow Length (in)	36	36

* Recommendations only for boats over 20'

NOTE: Measurements are approximations only. Variations will occur due to tolerances in manufacturing