



STANDARD FEATURES
PRO V

EFFECTIVE SEPTEMBER 1, 2020

WWW.HEWESCRAFT.COM

	PV	PV HT
Battery Selector Switch	standard	standard
Bilge Pump: Single bilge pump with auto switch	standard	standard
Bow Eye: Double, welded	standard	standard
Bow Deck: Treadplate, self-bailing, with storage	standard	standard
Bow Rails: 12" aluminum	N/A	standard
Canvas: Fish curtain; black, gray	N/A	standard
Cleats: 8", welded	5	7
Cup Holders: Port and starboard	standard	standard
Decals: 15" vinyl side striping with graphics; black, white, blue, yellow, green, red, orange, charcoal	standard	standard
Door: Walk through, access to bow, 2 latches, one top and one bottom	standard	standard
Fish Box: 26 gallon in bow floor	standard	standard
Fuel System: 48 gallons	standard	standard
Glove Box: Lockable	standard	standard
Grab Handles: Inwale front port side, glove box and windshield	standard	standard
Handrails: Vertical, aft cabin sides	N/A	standard
Horn: Flush mount	standard	standard
Instrument Panel:	standard	standard
-Six water-resistant rocker style switches		
-Fuel gauge and one panel knock-out for additional gauge		
-Power point		
-Six-gang expansion fuse block		
Light: LED, interior, overhead	N/A	standard
Lights: LED, navigational	standard	standard
Lights: LED, anchor, removable	standard	standard
Pre-rig: Side mount control with analog tach	standard	standard
Rail: Cabin Top	N/A	standard
Seats: High-back, dry box with lid, swivel, horseshoe suspension	standard	standard
Steering: No feedback	standard	standard
Steering Wheel: Stainless steel with rubber grip	standard	standard
Stern Eyes: Welded, port and starboard	standard	standard
Storage Shelves: Under driver & passenger consoles	standard	standard
Storage Trays: Port and starboard	standard	standard
Storage Trays: Overhead, port and starboard	N/A	standard
Transducer Bracket: Port and starboard	standard	standard
Transom: 25" -shaft main engine and 20" -shaft kicker	standard	standard
Wave board: At motorwell	standard	standard
Windows: Sliding, port and starboard	N/A	standard
Wipers: Port and starboard	optional	standard



STANDARD FEATURES PRO V ET

EFFECTIVE SEPTEMBER 1, 2020

WWW.HEWESCRAFT.COM

	PV ET	PV ET with SLC
Battery Selector Switch	standard	standard
Bilge Pump: Single bilge pump with auto switch	standard	standard
Bow Eye: Double, welded	standard	standard
Bow Deck: Treadplate, self-bailing, with storage	standard	standard
Bow Rails: 12" aluminum	N/A	standard
Canvas: Fish curtain; black, gray	N/A	standard
Cleats: 8", welded	5	7
Cup Holders: Port and starboard	standard	standard
Decals: 15" vinyl side striping with graphics; black, white, blue, yellow, green, red, orange, charcoal	standard	standard
Door: Walk through, access to bow, 2 latches, one top and one bottom	standard	standard
Fish Box: 26 gallon in bow floor	standard	standard
Fuel System: 48 gallons	standard	standard
Glove Box: Lockable	standard	standard
Grab Handles: Inwale front port side, glove box and windshield	standard	N/A
Handrails: Vertical, aft cabin sides	N/A	standard
Horn: Flush mount	standard	standard
Instrument Panel:	standard	standard
-Six water-resistant rocker style switches		
-Fuel gauge and one panel knock-out for additional gauge		
-Power point		
-Six-gang expansion fuse block		
Light: LED, interior, overhead	N/A	standard
Lights: LED, navigational	standard	standard
Lights: LED, anchor, removable	standard	standard
Paint: Light gray, full inside	standard	standard
Pre-rig: Side mount control with analog tach	standard	standard
Rail: Cabin Top	N/A	standard
Rod Grippers: Inwale, port and starboard	standard	standard
Seats: High-back, dry box with lid, swivel, horseshoe suspension	standard	standard
Steering: Hydraulic, Baystar, 150HP or less	standard	standard
Steering Wheel: Stainless steel with rubber grip	standard	standard
Stern Eyes: Welded, port and starboard	standard	standard
Storage Shelves: Under driver & passenger consoles	standard	standard
Storage Trays: Cockpit, inwale and under console, port and starboard	standard	standard
Storage Trays: Overhead, port and starboard	N/A	standard
Transducer Bracket: Port and starboard	standard	standard
Transom: 25" -shaft main engine and 20" -shaft kicker	standard	standard
Windows: Sliding, port and starboard	N/A	standard
Wipers: Port and starboard	optional	standard